

EMT Elbows

30° - Galvanized Steel

Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit


Standard Material

- Galvanized steel



E197604

UL 797 and ANSI C80.3
Federal Specification WW-C-563



| Catalog Number | UPC | Size | Unit Carton | Ship Case | Weight/Case | (A) Min. UL Radius | (B) Straight Leg Each End |
|----------------|-------|---------------|-------------|-----------|-------------|--------------------|---------------------------|
| 8430 | 83903 | 1-1/4" | --- | 30 | 19 | 7.25 | 2.781 |
| 8530 | 83893 | 1-1/2" | --- | 15 | 25 | 8.25 | 2.781 |
| 8630 | 83905 | 2" | --- | 10 | 20 | 9.5 | 2.781 |
| 8730 | 83906 | 2-1/2" | 1 | 50 | 161 | 10.5 | 3 |
| 8830 | 83907 | 3" | 1 | 35 | 153 | 13 | 3.125 |
| 8930 | 83908 | 3-1/2" | 1 | 35 | 244 | 15 | 3.281 |
| 89A30 | 83909 | 4" | 1 | 35 | 309 | 16 | 3.375 |