



# Standard Grade Plugs and Connectors

2 Pole, 2 Wire Non-Grounding  
NEMA 1-15, 15A 125V


## Rubber Plugs and Connectors

### FEATURES

- Angle plugs allow placement of cord in convenient location.
- Plug blades are firmly embedded in body.
- Terminal screws backed out —ready for wiring.

INDUSTRIAL  
COMMERCIAL  
RESIDENTIAL

## I-19 STRAIGHT BLADE PLUGS AND CONNECTORS



84



86



183

### Rubber Plugs and Connectors

Rating A	V/AC	NEMA	Description	Cord Diameter	Color	Catalog No.	
						Plug	Connector
15	125	1-15	Angle	0.328" (8.33mm)	Black	84BK	86BK
					White	84W	86W
15	125	1-15	Angle Polarized	0.328" (8.33mm)	Black	84-6BK	86BK
					White	84-6W	86W
15	125	1-15	Straight	0.328" (8.33mm)	Black	183BK	86BK
					White	183W	86W
15	125	1-15	Straight Polarized	0.328" (8.33mm)	Black	183-6BK	86BK
					White	183-6W	86W

### TESTING & CODE COMPLIANCE

- Listed to UL 498 (file no. E15012).
- Polarized plugs: CSA Certified to C22.2 no 42. (file no. LR2081 (6221-02, 6221-82)).
- NOM Certified.

### MATERIAL CHARACTERISTICS

Thermoplastic  
Rubber.  
Temperature Rating:  
-20°C to 70°C.



1-15P



1-15R