


# Specification grade GFICs

## Specification grade ground fault circuit interrupter receptacles

### Product description

2-pole, 3-wire grounding  
15A, 125V/AC; 20A, 125V/AC  
NEMA 5-15, 5-20



SGF15



SGFS15



SGFD20

### Specification grade GFICs



Rating	A	V/AC	NEMA	Description	Color suffix	Catalog no.	
15	125	5-15R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, V, W	<input type="checkbox"/> SGF15__	•	
			Duplex GFCI, mid-size wallplate, back & side wire	A, LA, V, W	<input type="checkbox"/> SGF15__-M		
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	<input type="checkbox"/> SGF15F__	• •	
20	125	5-20R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, RD, V, W	<input type="checkbox"/> SGF20__	•	
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	<input type="checkbox"/> SGF20F__	• •	

Includes standard size unbreakable wallplate unless otherwise noted  
Consult factory customer service representative for additional packaging options

### Specification grade combination GFCI receptacle & switch



Rating	A	V/AC	NEMA	Description	Color suffix	Catalog no.
15	125	5-15R		GFCI receptacle with feed-through single-pole switch (rated 1800W @ 120V/AC, 60Hz)	A, LA, V, W	<input type="checkbox"/> SGFS15__-MSP

### Specification grade blank face GFCI



Rating	A	V/AC	Description	Color suffix	Catalog no.
20	125		Blank face (dead front) GFCI, rated as 1.5HP motor control switch, back & side wire	A, BK, LA, V, W	<input type="checkbox"/> SGFD20__

### Accessories for GFCIs

Description	Color suffix	Catalog no.	
GFCI 7/8" extension ring, cULus Listed	BLK, LA, V, W	<input type="checkbox"/> GFER__	
Metal self-closing horizontal 1-gang weather protective cover, decorator opening		<input type="checkbox"/> S1966	•
While-in-use metal weather protective standard depth 1-gang cover, vertical mount		<input type="checkbox"/> WIUMV-1	•



GFER



S1966



WIUMV-1



WIUMH-1

### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

<b>A</b>	<b>B</b>	<b>BK</b>	<b>GY</b>	<b>LA</b>	<b>RD</b>	<b>V</b>	<b>W</b>
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

ArrowLink option available. Add "MOD" suffix to standard catalog number (example VGF15W, VGF15WMOD). For ordering information on ArrowLink & ArrowLink SPD connectors

Indicates NAFTA compliant

Tamper resistant

**Specification information:** Page 9 & 10

**Compliances, specifications and availability are subject to change without notice.**