

5', 6', & 8'

OSHA & ANSI COMPLIANT COMBINATION LADDER

1. ONE-HANDED GRIP-N-GO HINGE

One-handed Grip-N-Go hinge operation allows for a quick and seamless transition between stepladder, extension, and leaning ladder configurations.

2. ROTATING WALL PAD

Get closer to your work with the rotating wall pad, which conforms to inside and outside corners, walls, poles, and 2x4 studs.

3. NON-CONDUCTIVE, HI-VIZ GREEN FIBERGLASS

Our Hi-Viz green fiberglass is lightweight and non-conductive. The color is proven to increase visibility, preventing injuries and accidents while in use.

4. QUAD POD[™]

The Quad Pod is a feature that is used in the extension ladder position, which allows the user to work on inside and outside corners, walls, poles, and studs.

5. DUAL-PURPOSE LEGS

Functional rear section allows access to tight workspaces between wall studs, ceiling trusses, and roof or attic access ports.

6. GROUND CUE[®]

Up to 20% of all ladder injuries happen from missing the bottom step while descending the ladder. Ground Cue makes an audible and tactile "click" that alerts you when you've reached the bottom rung.



NON-CONDUCTIVE FIBERGLASS
FIBRA DE VIDRIO NO CONDUCTORA





Inside Corner Rotating Wall Pad



One-Handed Grip-N-Go Hinge



Quad Pod On Flat Wall



Outside Corner Rotating Wall Pad



Fit Between Studs & Other Tight Workspaces



Extension



Quad Pod On Outside Corner

PRODUCT DESCRIPTION

It's the pro tool that helps you get stuff done faster than ever. The pinnacle of ladder technology, the King Kombo™ from Little Giant Ladder Systems® is tough as nails and versatile enough for any tradesman. Recognized for its superior safety and innovation, the King Kombo is the most awarded ladder ever, having received awards at the 2019 Pro Tool Innovation Awards, 2019 OH&S New Product of the Year Awards, SAFE Awards from the National Association of Homebuilders, and more.

1-YEAR LIMITED WARRANTY

Part #	Model	Stepladder Highest Standing Level	Stepladder Max Reach*	Extension Highest Standing Level	Extension Max Reach*	Spread	Storage Width at Base	Storage Depth	Weight
13905-071	5	2' 10"	9' 4"	4' 10"	11' 4"	3'	2' 5"	7"	19 lbs
13906-071	6	3' 9"	10' 3"	6' 7"	13' 1"	3' 8"	2' 1"	7"	23 lbs
13908-071	8	5' 8"	12' 2"	10' 8"	17' 2"	4' 11"	2' 4"	7"	31 lbs

*A 5' 6" person with a 12" vertical reach