Specifications

| Drill Bit Size (Inch) | 17/64 |
|-------------------------------|------------------------------------|
| Drill Bit Size (Decimal Inch) | 0.2656 |
| Drill Bit Size | 0.2656in |
| Drill Point Angle | 135? |
| Drill Bit Material | High Speed Steel; High Speed Steel |
| Drill Bit Finish/Coating | Coated; Oxide |
| Flute Type | Spiral |
| Cutting Direction | Right Hand |
| Tool Material | High Speed Steel |
| Shank Type | Straight Shank |
| Coated | Coated |
| Coolant Through | None; No |

| Drill Bit Size Range (Decimal Inch) | 0.2500 - 0.3000 |
|-------------------------------------|------------------------------------|
| Series | R10B |
| Tool Application | Centering |
| Shank Size | 0.2656in |
| Flute Length (Inch) | 2-7/8 |
| Overall Length (Inch) | 4-1/8 |
| Tool Performance | High Performance |
| Primary Workpiece Material | Nickel; Titanium |
| Point Type | Split Point |
| Primary Workpiece Material Code | H; K; P; S |
| Secondary Workpiece Material | Aluminum Magnesium; Copper; Nickel |
| Shank Diameter (Decimal Inch) | 0.2656in |
| Secondary Workpiece Material Code | H; K; M; N; P; S |

| Standards | ANSI |
|---------------------------|----------------|
| Spiral Type | Regular Spiral |
| Specification Designation | ANSI; NAS |
| Web Configuration | Tapered |
| Web Thinning | Web-Thinned |
| Specification Number | NAS 907 |
| Drill Bit Grade | Heavy Duty |
| Series/List | R10B |