Specifications

| Drill Bit Size (Inch) | 21/64 |
|-------------------------------|------------------------------------|
| Drill Bit Size (Decimal Inch) | 0.3281 |
| Drill Bit Size | 0.3281in |
| Drill Point Angle | 118? |
| Drill Bit Material | High Speed Steel; High Speed Steel |
| Drill Bit Finish/Coating | Coated; Oxide |
| Flute Type | Spiral |
| Cutting Direction | Right Hand |
| Tool Material | High Speed Steel |
| Shank Type | Straight Shank |
| Coated | Coated |
| Coolant Through | None; No |

| Drill Bit Size Range (Decimal Inch) | 0.3000 - 0.3500 |
|-------------------------------------|---|
| Series | R10 |
| Shank Size | 0.3281in |
| Flute Length (Inch) | 3-5/16 |
| Overall Length (Inch) | 4-5/8 |
| Tool Performance | General Purpose |
| Primary Workpiece Material | Cast Iron; Steel |
| Point Type | Standard |
| Primary Workpiece Material Code | K; P |
| Secondary Workpiece Material | Aluminum Magnesium; Copper; Nickel; Synthetic; Titanium |
| Shank Diameter (Decimal Inch) | 0.3281in |
| Secondary Workpiece Material Code | H; K; M; N; O; P; S |
| Shank Size (Inch) | 0.3281in |

| Spiral Type | Regular Spiral |
|---------------------------|-----------------|
| Specification Designation | ANSI |
| Web Configuration | Tapered |
| Web Thinning | Web-Thinned |
| Drill Bit Grade | General Purpose |
| Series/List | R10 |