



Specifications

Cat. No.	Watts	BTU	Available Voltages	Phase	Length mm/in.	Weight kg/lbs.
AF6F205	500	1706	120, 208, 240, 347	1	616 / 24 5/16	3.9 / 8.5
AF6F307	750	2559	120, 208, 240, 347, 600	1	921 / 36 5/16	5.2 / 11.5
AF6F410	1000	3412	120, 208, 240, 347, 600	1	1223 / 48 5/16	6.6 / 14.6
AF6F512	1250	4265	120, 208, 240, 347, 600	1	1530 / 60 5/16	8.3 / 18.2
AF6F615	1500	5118	120, 208, 240, 347, 600	1	1835 / 72 5/16	10 / 22
AF6F717	1750	5971	208, 240, 347, 600	1	2140 / 84 5/16	11.9 / 26
AF6F820	2000	6824	208, 240, 347, 600	1	2445 / 96 5/16	13.8 / 30.5
AF6F922	2250	7677	208, 240, 347, 600	1	2750 / 108 5/16	16 / 35
AF6F025	2500	8530	208, 240, 347, 600	1	3054 / 120 5/16	18.3 / 40

1. Specify desired voltage, finish and control option from tables
2. For bottom inlet version replace "F" in Cat. No. with "B"
3. Endcaps are included with heaters
4. Consult factory for custom finish requirements

Voltage Selection

Code	Voltage	Phase
11	120	1
21	208	1
31	240	1
51	347	1
81	600	1

Finish Selection

Code	Colour	Finish
02	White	Painted
68	Almond	Painted
07	Bronze	Anodized
10	Clear	Anodized

Cabinet Features

Code	Description
W	Pedestal and finished painted black
S	Finished painted black

Note: add "S" or "W" to the end of the Cat. No.

Control Options (factory installed)

Cat. No.	Description
A1	Built-in SP tamperproof thermostat 120 - 600V
A2	Built-in DP tamperproof thermostat 120 - 600V
F1	Built-in SP tamperproof thermostat 120 - 600V (side mounted)
F2	Built-in DP tamperproof thermostat 120 - 600V (side mounted)
A4	Built-in 24V low voltage relay 120 - 600V
A5	Built-in 24V low voltage relay and transformer 120 - 600V
A8	Built-in disconnect switch, rated 277V/20A
B1	Built-in SP tamperproof thermostat and disconnect
B2	Built-in DP tamperproof thermostat and disconnect
F3	Built-in SP adjustable thermostat and disconnect
F4	Built-in DP adjustable thermostat and disconnect
D1	Built-in low voltage relay and disconnect
D2	Built-in low voltage relay / transformer and disconnect

Accessories* (field installed)

Cat. No.	Description
ALF61C90	Inside 90 degree corner
ALF60C90	Outside 90 degree corner
Filler Sections	Consult factory for available sizes

* Note: Specify "Finish selection" code (see "Finish Selection" chart) when ordering accessories

Pedestal Options*

Cat. No.	Description
ALPKS2	Pedestal kit for units up to 4' length (2 pedestals included)
ALPKS3	Pedestal kit for units up to 4' length (3 pedestals included)

* Note: Specify "Finish selection" code (see "Finish Selection" chart) when ordering accessories

Dimensions

