HellermannTyton

Specification Sheet

Part Number: 181-91510



A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.

Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Article Number	181-91510
Туре	TC1.5
Color	White (WH)
Quantity Per	carton
Product Description	HellermannTyton's Pro-Duct wiring duct covers are sold separately and interchangeable among the 3 styles of duct (solid, slotted and high density). Manufactured from high impact, rigid PVC, Pro-Duct covers come in standard colors of white, gray and black. Wiring duct covers are available in 6 foot lengths.
Short Description	Wiring Duct Cover for 1-1/2" Duct, 6 ft Long, PVC, White, 120 ft/carton

Global	Part	Name
--------	------	------

Technical DescriptionWiring Duct Cover for 1 1/2" Duct, White

Length L (Imperial)	6.0
---------------------	-----

- Length L (Metric) 1.83
- Width W (Imperial) 1.5
- Width W (Metric) 38.1
- Height H (Imperial) 0.308
- Height H (Metric) 7.82

Material

Material Shortcut

Flammability

Halogen Free

No

No

PVC

Operating Temperature

+122°F (+50°C)

Self-extinguishing

Polyvinylchloride (PVC)

Reach Compliant (Article 33)

ROHS Compliant	Yes
Certification/Specification	UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A
UL Recognized (US)	Yes
Package Quantity (Imperial)	120
Package Quantity (Metric)	36.58
Customs Number	3925900000

© 2022 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions