

Industrial grade AC toggle switches with
CuVerro® antimicrobial copper surface.




Product description

Single-pole, double-pole, 3-way, 4-way
15A, 120/277 V/AC; 20A, 120/277 V/AC

Toggle switches

Rating					
A	V/AC	Description	Color suffix	Catalog no.	
20	120/277	Single-pole switch w/ CuVerro® toggle	CU, CUR	☐ AH1221__	✓
20	120/277	Double-pole switch w/ CuVerro® toggle	CU, CUR	☐ AH1222__	✓
20	120/277	3-Way switch w/ CuVerro® toggle	CU, CUR	☐ AH1223__	✓
20	120/277	4-Way switch w/ CuVerro® toggle	CU, CUR	☐ AH1224__	✓

Compliant with: cULus & FULS



Industrial grade AC three-position switches

Product description

15A, 120/277V/AC; 20A, 120/277V/AC
Maintained & momentary contact
Single-pole, double-pole

AC maintained contact toggle switches, back & side wire



Rating					
A	V/AC	Description	Color suffix	Catalog no.	
20	120/277	Single-pole, maintained contact toggle, center off	V	☐ 2225V*	✓
		Double-pole, maintained contact toggle, center off	B, V	☐ 2226__*	✓

*Not CSA certified

AC momentary contact switches, back & side wire



Rating					
A	V/AC	Description	Color suffix	Catalog no.	
15	120/277	Single-pole, momentary contact toggle, center off	B, GY, V	☐ 1895__	✓
		Single-pole, momentary contact locking, center off, nickel locking dome		☐ 1895L	✓
20	120/277	Single-pole, momentary contact toggle, center off	B, GY, RD, V	☐ 1995__	✓
		Single-pole, momentary contact toggle, center off	W	☐ AH1995W	✓
		Single-pole, momentary contact locking, center off, nickel locking dome		☐ 1995L	✓

Accessories for industrial grade maintained & momentary switches

Description	Catalog no.	
Replacement key for locking switches, 1895L & 1995L	☐ AH2000	✓
1-Gang, standard size, toggle, 302/304 stainless steel wallplate	☐ 93071	✓
1-Gang, standard size, toggle, unbreakable nylon wallplate	☐ 5134V	✓



AH2000



93071



5134V

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), GY (Gray), RD (Red), V (Ivory), W (White)

B	GY	RD	V	W
(Brown)	(Gray)	(Red)	(Ivory)	(White)

Specification information: 120/277V CuVerro® toggle switches: E-42, 120/277V Industrial maintained & momentary contact: E-34
Compliances, specifications and availability are subject to change without notice.