

## 601109420, Metabo KHE D-26, 1in SDS-Plus Rotary Hammer, 2.3J

### Features:

- Combination hammer with 3 functions: hammer drilling, drilling, and chiseling
- Spade handle for the best working comfort and maximum productivity when working low down or above the head
- Vario (V)-electronics for working at customized speeds to suit various application materials.
- High performance hammer action, precisely mounted in a housing made of aluminum alloy: long-lasting and robust
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- Lockable switch for trouble-free working in continuous operation
- Frame hook for easily and securely storing hammers on frames and ladders

### Specifications:

- Max. single blow energy (EPTA) 2.3 J
- Amps 7 AMPS
- Maximum impact rate 5400 BPM
- Rated input power 800 W
- Max. capacity in concrete with hammer drills 1 "
- Max. capacity in masonry with core bits 2 5/8 "
- Max. capacity in steel 1/2 "
- Max. capacity in soft wood 1 3/16 "
- No-load speed 0 - 1150 RPM
- Revolutions at rated load 960 RPM

- Bit retainer SDS-plus
- Collar diameter 1 11/16 "
- Weight (without power cable) 6.4 lbs
- Cable length 13 ft
- Hammer drilling concrete 13.7 m/s<sup>2</sup>
- Uncertainty of measurement K 1.5 m/s<sup>2</sup>
- Chiseling 15 m/s<sup>2</sup>
- Uncertainty of measurement K 1.5 m/s<sup>2</sup>
- Sound pressure level 87 dB(A)
- Sound power level (LwA) 98 dB(A)
- Uncertainty of measurement K 3 dB(A)

**Includes:**

- Hammer chuck for tools with SDS-plus shank end
- Side Handle
- Drilling depth guide
- Plastic carrying case