

## BRU400A

ABB contact for United  
States of America



### General Information

---

<b>Extended Product Type:</b>	BRU400A
<b>Product ID:</b>	1SNA179650R2200
<b>EAN:</b>	3472591796506
<b>Catalog Description:</b>	BRU400A Distribution Terminal Blocks
<b>Long Description:</b>	BRU400A Distribution Terminal Blocks - Grey, 44.5mm Spacing TH 35-7.5, TH 35-15 Rail

---

### Categories

---

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Distribution Terminal Blocks

---

### Ordering

---

<b>EAN:</b>	3472591796506
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369010

---

### Dimensions

---

<b>Product Net Width:</b>	44.5 mm
<b>Product Net Height:</b>	96.0 mm
<b>Product Net Depth:</b>	44.5 mm
<b>Product Net Weight:</b>	415.00 g

---

### Container Information

---

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Length:</b>	44.5 mm
<b>Package Level 1 Gross Weight:</b>	0.41500 kg
<b>Package Level 1 EAN:</b>	3472591796506
<b>Package Level 2 Units:</b>	20 piece
<b>Product Packing Type:</b>	Box
<b>Packing Type:</b>	Box

---

### Environmental

---

<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

---

### Technical UL/CSA

---

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
<b>Tightening Torque UL/CSA:</b>	Main Circuit 230 ... 265 in·lb
<b>Short-Circuit Current Rating (SCCR):</b>	100 kA

---

### Additional Information

---

<b>Color:</b>	Grey
<b>Connecting Capacity-Main Circuit:</b>	Screw Clamp / Rigid 1x 95 ... 185 mm <sup>2</sup>
<b>Connection Type:</b>	Screw clamp
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
<b>Function:</b>	Feed-through

<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Number of Levels:</b>	1
<b>Product Main Type:</b>	BRU
<b>Product Name:</b>	Terminal Block
<b>Rated Cross-Section:</b>	150 mm <sup>2</sup>
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	for 1.0s 21 A
<b>Spacing:</b>	44.5 mm
<b>Sub-Function:</b>	1 pôle
<b>Wire Stripping Length:</b>	28.0 mm

---

### Certificates and Declarations (Document Number)

---

<b>CSA Certificate:</b>	1SND166003A0201
<b>Declaration of Conformity - CE:</b>	1SND225033C1006
<b>GOST Certificate:</b>	1SND161005A1104
<b>RoHS Information:</b>	1SND230013F0202

---

### Classifications

---

<b>ETIM 4.0:</b>	EC000276 - Distribution terminal block
<b>ETIM 5.0:</b>	EC000276 - Distribution terminal block
<b>Object Classification Code:</b>	X

---