

LyteCaster Accent

round & square apertures



Design versatility to fit any space.

Available in a variety of round and square accent styles and finishes with efficacies ranging up to 800 lm/W. A wide range of options that allow you to customize your lighting solution to best suit the application.

Features

- Sizes: 3"
- Efficacy: up to 72 lm/W
- Lumens: 800
- Wattage: 11W
- Voltage: 120V or 120V-277V
- CCT: 2700K-3500K
- CRI: 80 & 90 min.
- Dimming: ELV/TRIAC (10%)
- 50,000 hour rated life (L70)

Housing



Light engine



Series / Size	Installations (Airseal IC)	Dimming	Voltage
L3	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
L3 LyteCaster 3-inch accent	A New construction with screws (Non-IC)	E ELV/TRIAC	1 120V
	AN New construction with nails (Non-IC)		
	C Remodeler (Non-IC) ¹		
	N New construction (Non-IC)	Z10 0-10V	U Universal 120/277V

Series / Size	Lumens	CRI / CCT	Beam	Option
L3	08	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
L3 LyteCaster 3-inch accent	08 800lm	827 80 CRI / 2700K	S Spot (17°)	— None
		830 80 CRI / 3000K	NF Narrow Flood (22°)	
		835 80 CRI / 3500K	F Flood (33°)	
	927 90 CRI / 2700K 930 90 CRI / 3000K ²	S Spot (17°)	CW CrispWhite ²	
		NF Narrow Flood (22°)		
		F Flood (33°)		

Trims



Series	Shape / Type	Style
L3	<input type="checkbox"/>	<input type="checkbox"/>
L3 LyteCaster 3-inch accent	RD Round / Downlight	C Chrome Cone with white flange D Diffuse Cone with white flange W White Cone with white flange
	RA Round / Adjustable ¹	
	RLW Round / Lensed Wall Wash ³	
	RB Round / Baffle Downlight	W White Baffle with white flange
	RAB Round / Baffle Adjustable	
	RAP Round / Adjustable Pinhole	A Aluminum B Black (gimbal only) W White
	RG Round / Gimbal ⁴	
	RS Round / Shower Light	
	SLW Square / Lensed Wall Wash ³	
	SS Square / Shower Light	
SD Square / Downlight	D Diffuse Cone with white flange DA Diffuse Cone with aluminum flange W White Cone with white flange (downlight only)	
SA Square / Adjustable ¹		

1. Remodeler frame is not compatible with adjustable trim.
2. The 3000K (30) and CrispWhite (CW) options must be ordered together.
3. Lensed wall wash (LW) is only available in Narrow flood (NF) and Flood (F) beam spreads
4. Gimbal (G) trims come with accessory holder (see spec sheets for complete listings of accessories).

Certifications: IC rated for direct contact with thermal insulation. Title 24 rated, cULus listed for wet locations, RoHS compliant, IP rated, ENERGY STAR[®] certified and featuring AirSeal for minimal air leakage.

