

INDUSTRIAL COMMERCIAL RESIDENTIAL

I-21
STRAIGHT BLADE
PLUGS AND
CONNECTORS

TESTING & CODE COMPLIANCE


· Listed to UL 498 (file no. E15012), cUL listed to CSA C22.2 no. 42 (file no. E15012) except SA155: CSA Certified (file no. LR2081 (6221-02, 622182)). · NOM Certified.

MATERIAL

CHARACTERISTICS
PVC and ABS.
Meets flammability
requirements
per UL 94, VO rated.
Temperature Rating:
-20°C to 60°C.









SA440W



SA540



SA940





1-15R

2 Pole, 2 Wire NEMA 1-15, 15A 125V

Spring Action Plugs and Connectors

FEATURES

 Clip provides cord grip for easy storage on appliances such as vacuum cleaners, fans, etc.

Plugs and Connectors

Standard Grade

Made of high impact-resistant thermoplastic for long-term durability.

Thermoplastic Plugs and Connectors							
Rating				Cord		Catalog No.	
Α	V/AC	NEMA	Description	Diameter	Color	Plug	Connector
15	125	1-15	Straight w/ Cord Clip	0.328" (8.33mm)	Black	SA840	SA155
					Brown	SA840B	SA155B
					White	SA840W	SA155W
15	125	1-15	Straight w/ Cord Clip Polarized	0.328" (8.33mm)	Black	SA940	SA155
					Brown	SA940B	SA155B
					White	SA940W	SA155W
15	125	1-15	Straight	0.328" (8.33mm)	Black	SA440	SA155
					Brown	SA440B	SA155B
					White	SA440W	SA155W
15	125	1-15	Straight Polarized	0.328" (8.33mm)	Black	SA540	SA155
					Brown	SA540B	SA155B
					Gold	SA540GD	SA155GD
					White	SA540W	SA155W