

## SPECIFICATION

<b>DIAMETER</b> 6-3/8 IN	<b>APPLICABLE MATERIALS</b> Acoustic Tile, Asbestos Board, Brick, Cast Iron, Cement Board, Ceramic, Cinderblock, Composites, Computer Flooring, Fiberglass, Formica, Hardened Steel and Particleboard
<b>DRILL SIZE</b> 1/4 IN DIA X 3-3/32 IN L	<b>CUTTING EDGE STYLE</b> Gulleted
<b>SERIES</b> MHSG	<b>SHANK TYPE</b> Hex
<b>CUTTING DEPTH</b> 1-15/16 IN	<b>CUTTING EDGE MATERIAL</b> Tungsten Carbide
<b>BODY MATERIAL</b> STEEL	<b>SHANK SIZE</b> 3/8 in
<b>ARBOR SIZE</b> 5/8-18	<b>USE ARBOR</b> MA35PSCT
<b>CHUCK SIZE</b> 3/8 IN	

## ADDITIONAL DESCRIPTION

For use on hard or abrasive materials including cement, brick, cinder block, cast iron, plaster with lath, unglazed ceramics, fiberglass, and composites.

### APPLICATIONS

- Acoustic tile
- Brick
- Cast iron
- Cement board
- Ceramics
- Cinderblock
- Composites
- Computer flooring
- Fiberglass
- Hardened steel

- Particleboard
- Asbestos board
- Formica

## BENEFITS

- Super resistance to heat, wear and abrasion with shock resistant back
- Tungsten carbide grains are bonded to alloy backs with a gulleted snag resistant edge
- CT pilot drill recommended for masonry type materials