

DIAMETER 3-5/8 IN	APPLICABLE MATERIALS Acoustic Tile, Asbestos Board, Brick, Cast Iron, Cement Board, Ceramic, Cinderblock, Composites, Computer Flooring, Fiberglass, Formica, Hardened Steel and Particleboard
DRILL SIZE 1/4 IN DIA X 3-3/32 IN L	CUTTING EDGE STYLE Gulleted
SERIES MHSG	SHANK TYPE Hex
CUTTING DEPTH 1-15/16 IN	CUTTING EDGE MATERIAL Tungsten Carbide
BODY MATERIAL STEEL	SHANK SIZE 3/8 in
ARBOR SIZE 5/8-18	USE ARBOR MA35PSCT
CHUCK SIZE 3/8 IN	SPEED 45 to 135 rpm

ADDITIONAL DESCRIPTION

For use on hard or abrasive materials including cement, brick, cinder block, cast iron, plaster with lath, unglazed ceramics, fiberglass, and composites.

APPLICATIONS

- Acoustic tile
- Brick
- Cast iron
- Cement board
- Ceramics
- Cinderblock
- Composites
- Computer flooring
- Fiberglass
- Hardened steel
- Particleboard
- Asbestos board
- Formica

BENEFITS

- Super resistance to heat, wear and abrasion with shock resistant back
- Tungsten carbide grains are bonded to alloy backs with a gulleted snag resistant edge
- CT pilot drill recommended for masonry type materials