

SPECIFICATION

| | |
|--|---|
| DIAMETER 4-1/8 IN | APPLICABLE MATERIALS Acoustic Tile, Asbestos Board, Brick, Cast Iron, Cement Board, Ceramic, Cinderblock, Composites, Computer Flooring, Fiberglass, Formica, Hardened Steel and Particleboard |
| DRILL SIZE 1/4 IN DIA X 3-3/32 IN L | CUTTING EDGE STYLE Gulleted |
| SERIES MHSG | SHANK TYPE Hex |
| CUTTING DEPTH 1-15/16 IN | CUTTING EDGE MATERIAL Tungsten Carbide |
| BODY MATERIAL STEEL | SHANK SIZE 3/8 in |
| ARBOR SIZE 5/8-18 | USE ARBOR MA35PSCT |
| CHUCK SIZE 3/8 IN | SPEED 40 to 120 rpm |

ADDITIONAL DESCRIPTION

For use on hard or abrasive materials including cement, brick, cinder block, cast iron, plaster with lath, unglazed ceramics, fiberglass, and composites.

APPLICATIONS

- Acoustic tile
- Brick
- Cast iron
- Cement board
- Ceramics
- Cinderblock
- Composites
- Computer flooring
- Fiberglass
- Hardened steel

- Particleboard
- Asbestos board
- Formica

BENEFITS

- Super resistance to heat, wear and abrasion with shock resistant back
- Tungsten carbide grains are bonded to alloy backs with a gulletted snag resistant edge
- CT pilot drill recommended for masonry type materials