



R531007

Baseline Twinleg Self Retracting Lifeline

FEATURES

- A100341 Twinleg Carabiner Adaptor
- 7 foot working range
- 1 inch Dyneema® / polyester webbing
- Aluminum housing
- Aluminum rebar hook has a gate opening of 2 ½ inches (63.5 mm)
- Steel rebar hook has a gate opening of 2 ⅞ inches (65 mm)
- Snap hooks, rebar hooks and carabiners are self-locking with a minimum tensile break strength of 5,000 pounds, and a 3,600 pound gate rating



SPECIFICATIONS

Model No.	Lifeline Connector	(A)	(B)	Depth	Aprox. Weight
R531007	Steel Snap Hook	14 ½ in (368 mm)	7 in (178 mm)	2 ¾ in (70 mm)	6.1 lb (2.8 kg)
R531007-R	Aluminum Rebar Hook	18 in (457 mm)	7 in (178 mm)	2 ¾ in (70 mm)	7.0 lb (3.2 kg)
R531007-SR	Steel Rebar Hook	18 ⅞ in (466 mm)	7 in (178 mm)	2 ¾ in (70 mm)	7.5 lb (3.4 kg)

COMPLIANCE STANDARDS

Meets	Maximum Arrest Distance	Average Arrest Force	Maximum Arrest Force	Free Fall Limit	Capacity
ANSI Z359.14-2012 CLASS B	36 in (914 mm)	900 lbf (4 kN)	1,800 lbf (8 kN)	24 in (610 mm)	130 - 310 lbs (59 - 141 kg)
OSHA 29 CFR 1910.140 & 1926.502	36 in (914 mm)	N/A	1,800 lbf (8 kN)	24 in (610 mm)	310 lbs (141 kg)

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed. Users MUST read and understand all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet

WERNER CO. CORPORATE HEADQUARTERS: 93 Werner Rd., Greenville, PA 16125-9499

TEL: 888-523-3370 FAX: (724) 588-0315 www.wernerco.com