

Rittal – The System.

Faster – better – worldwide.

► Catalog 33
North American Edition 2012

50

Rittal. Power and Vision!

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

Outlet filter

For ventilation by convection, an outlet filter can be installed in the upper and lower sections of the enclosure.

Material:

ABS, material resistance to UL 94-V0

Color:

RAL 7035

Configuration:

- Outlet filter
- Filter mat

Dimensions H x W x D inches (mm)	Part No.	
	Standard	EMC
5 x 5 x .6 (116.5 x 116.5 x 16)	3237.200	3237.060
6 x 6 x .9 (148.5 x 148.5 x 24)	3238.200	3238.060
8 x 8 x .9 (204 x 204 x 24)	3239.200	3239.060
10 x 10 x .9 (255 x 255 x 25)	3240.200	3240.060
13 x 13 x .9 (323 x 323 x 25)	3243.200	3243.060

Accessories:

- Spare filter mats, see page 483
- Fine filter mats, see page 484



Blanking cover

If existing mounting cut-outs for filter fan/outlet filters need to be closed to achieve a higher protection category, the filter mat can simply be replaced with a blanking cover; welding or other mechanical modification of the enclosure is not necessary.


Material:

Plastic

Protection rating:

IP 54

For	Packs of	Part No.
3237. . . .	2	3237.080
3238. . . .	2	3238.080
3239. . . .	2	3239.080
3240. . . . 3241. . . .	2	3240.080
3243. . . . 3244. . . .	2	3243.080



Front outlet grill 2 U for tangential fans

This front outlet grill is required if a 19" (482.6 mm) cross-flow blower (3144.000/3145.000) is used in the lower section of the electronic enclosure and the hot air is to be expelled to the outside from the upper section of the enclosure. The design of the grill matches that of the intake grill in the cross-flow blower. These grills can also be used as simple inflow and outflow grills with natural convection.

Accessories:

Filter mat, see page 481

Packs of	Part No.
1	3176.000



Filter holder for roof ventilation

The use of a filter mat is required in order to increase the protection category of the roof vent (3148.007). Protection rating IP 44 to IEC 60 529 is achieved.

Material:

Carbon steel

Configuration:

Filter holder including filter mat

Accessories:

Spare filter mat, see page 483

H x W x D inches (mm)	Part No.
10 x 13 x 1 (244 x 340 x 15)	3175.000

