



HAND PROTECTION

Performance Chemical and Cut Resistant Gloves

DESCRIPTION

These 12-inch long double-dipped on PVC and nitrile gloves feature a seamless, 15-gauge Aralene® (enhanced aramid fiber) liner. The gloves are enhanced with a sandpaper grip dipped palm. Nitrile provides chemical resistance and blended with 70% PVC, adds additional flexibility.

INDUSTRY

Light Metal Fabrication	Handling Oily Components
Parts Handling	Maintenance
Chemical Handling	



FEATURES

- 15-gauge Aralene® sewn liner offers cut and high temperature resistance
- Premium 30% nitrile and 70% PVC blended shell
- Sandpaper finish enhances grip in wet or oily situations
- 12-inch length for extra arm protection
- Overcast color on hem for easy size identification

ITEM CR292

- Gauntlet cuff allows for easy donning and removal plus extra forearm protection
- ANSI Cut Level A3
- ASTM F2992-15 Results = 1,357 grams
- ANSI Abrasion Level 5
- EN 388 Levels: 3X31C
- EN 374 Levels: AJKL
- EN 407 Levels: X1XXXX

SIZES 8(M)-10(XL)



SPECIFICATIONS

LINER	GAUGE	COATING TYPE	FINISH	CUFF	ANSI CUT	ASTM F2992-15 RESULTS	ANSI ABRASION	EN 388 LEVELS	EN 374 LEVELS	EN 407 LEVELS
Aralene®	15-Gauge	Double-Dipped	Sandpaper	Gauntlet	Level A3	1,357 Grams	Level 5	3X31C	AJKL	X1XXXX

PACKAGING

	QUANTITY	8(M)	9(L)	10(XL)
PAIR UPC	1	N/A	N/A	N/A
INNER PACK UPC	12/PACK	810292029364	810292029374	810292029388
CASE GTIN	6 PK/CASE	10810292029361	10810292029378	10810292029385
CASE WEIGHT (IN POUNDS)		31	33	35
OVERCAST COLOR		GREEN	BROWN	BLACK

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com


Global Glove
& Safety Manufacturing, Inc.