



Industrial grade AC three-position switches

Product description


15A, 120/277V/AC; 20A, 120/277V/AC
 Maintained & momentary contact
 Single-pole, double-pole



1205



1995



1995L

AC maintained contact toggle switches, back & side wire



Rating	A	V/AC	Description	Color suffix	Catalog no.	USA	RoHS
20	120/277		Single-pole, maintained contact toggle, center off	V	□ 2225V	•	•
			Double-pole, maintained contact toggle, center off	B, V	□ 2226__	•	•

AC momentary contact switches, side wire



Rating	A	V/AC	Description	Color suffix	Catalog no.	USA	RoHS
15	120/277		Single-pole, momentary contact toggle, center off	B, GY, V	□ 1895__	•	•
			Single-pole, momentary contact locking, center off, nickel locking dome		□ 1895L	•	•
20	120/277		Single-pole, momentary contact toggle, center off	B, GY, RD, V	□ 1995__	•	•
			Single-pole, momentary contact toggle, center off	W	□ AH1995W	•	•
			Single-pole, momentary contact locking, center off, nickel locking dome		□ 1995L	•	•

Accessories for industrial grade maintained & momentary switches

Description	Catalog no.	USA	RoHS
Replacement key for locking switches, 1895L & 1995L	□ AH2000	•	
1-Gang, standard size, toggle, 302/304 Stainless steel wallplate	□ 93071	•	•
1-Gang, standard size, toggle, unbreakable nylon wallplate	□ 5134V	•	•



AH2000



93071



5134V

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), GY (Gray), RD (Red), V (Ivory), W (White)



Specification information: 120/277V Industrial maintained & momentary contact: E-34
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32