

Industrial Specification Grade Plugs and Connectors

2-Pole, 3-Wire Grounding
NEMA 5-15, 15A 125V
NEMA 6-15, 15A 250V
NEMA 5-20, 20A 125V
NEMA 6-20, 20A 250V



H-6 Straight Blade Plugs & Connectors




AutoGrip™ Nylon Dead-Front Plugs and Connectors

FEATURES

- Neoprene gasket seals cord hole opening.
- Back wired for easy installation.
- All nylon construction reduces breakage and provides excellent chemical resistance.
- Automatic cord grip clamps the cord during assembly.

AutoGrip™ Dead-Front Plugs and Connectors

Rating		Description		Cord	Color	Catalog No.	
A	V/AC	NEMA		Diameter		Plug	Connector
15	125	5-15	Straight	0.250-0.656" (6.4-16.7mm)	Black & White	5266N	5269N
			Straight Corrosion Resistant	0.250-0.656" (6.4-16.7mm)	Yellow	5266NCR	5269NCR
15	250	6-15	Straight	0.250-0.656" (6.4-16.7mm)	Black & White	5666N	5669N
20	125	5-20	Straight	0.250-0.656" (6.4-16.7mm)	Black & White	5366N	5369N
			Straight Corrosion Resistant	0.250-0.656" (6.4-16.7mm)	Yellow	5366NCR	5369NCR
			Straight	0.250-0.656" (6.4-16.7mm)	Yellow	5366NY	5369NY
20	250	6-20	Straight	0.250-0.656" (6.4-16.7mm)	Black & White	5466N	5469N



TESTING & CODE COMPLIANCE

- Listed to UL 498 (file no. E3663).
- UL verified to Federal Spec. WC-596.
- cUL listed to C22.2 no 42.

MATERIAL CHARACTERISTICS

Nylon, except 5757 & 5783: ABS/PVC.
Temperature Rating: -40°C to 75°C.