

Hart lock industrial grade 15A locking devices

Product description

2-pole, 3-wire grounding
15A, 125V/AC
NEMA L5-15



L5-15R



L5-15P



CWL515C

Industrial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	125	L5-15	Safety grip straight body	0.33-0.66" (8.4-16.7mm)	BK & W	☐ CWL515P	☐ CWL515C	•	•
			Safety grip angled body	0.33-0.66" (8.4-16.7mm)	BK & W	☐ CWL515PAN	☐ CWL515CAN	•	•
			Auto grip	0.33-0.66" (8.4-16.7mm)	BK & W	☐ 4721N	☐ 4731N	•	•

Industrial grade receptacles



Rating A	V/AC	NEMA	Description	Color	Single receptacle	Duplex receptacle		
15	125	L5-15	Standard industrial	BK	☐ CWL515R*	—	•	•
			Standard industrial	BK	—	☐ 4700	•	•
			Isolated ground	RN	☐ IGL515R*	☐ IG4700*	•	•
		5-15	Combination locking & straight blade	BK	—	☐ 5792*	•	•

*Not Fed Spec

Industrial grade flanged inlet



Rating A	V/AC	NEMA	Description	Color	Flanged inlet		
15	125	L5-15	Standard industrial	BK & W	☐ CWL515FI	•	•

Industrial grade flanged outlet



Rating A	V/AC	NEMA	Description	Color	Flanged outlet		
15	125	L5-15	Standard industrial	BK & W	☐ CWL515FO	•	•

Dimensional information:
C-76-C-78

Plug & connector specification information:

Safety grip K5-15: C-84

Auto grip K5-15: C-84

Receptacle specification information:

K5-15: C-86

Isolated ground K5-15: C-86

Flanged inlet & flanged outlet specification information:

K5-15: C-88

Color information:

BK (Black), RN (Orange), W (White)

BK	RN	W
(Black)	(Orange)	(White)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30

RoHS compliant - Page Q-30