

Range and Dryer Plugs and Connectors – for Replacement Use Only

3 Pole, 3 Wire Non-Grounding
NEMA 10-30, 30A 125/250V
NEMA 10-50, 125/250V



INDUSTRIAL
COMMERCIAL
RESIDENTIAL

I-26 STRAIGHT BLADE PLUGS AND CONNECTORS

TESTING & CODE COMPLIANCE

- Listed to UL 498 Plugs: (file no. E15012)
- Receptacles: (file no. E15058).
- CSA Certified to C22.2 no. 42 (file no. LR7087), except as noted.

MATERIAL CHARACTERISTICS

Plugs: Nylon and Polypropylene.
Angle Plugs: Nylon and ABS, except 80: PVC.
Receptacles: Urea and polypropylene
Environmental: Flammability per UL 94 requirements, AutoGrip plugs, connectors and inlets: V2 rated. 80: V0 rated.
Temperature Rating: -40°C to 75°C, except: 80, -20°C to 60°C.



Industrial Specification Grade Range and Dryer Devices – for Replacement Use Only

FEATURES

- Neoprene gasket seals cord hole opening on AutoGrip™ connector; prevents dust/moisture from entering wiring chamber.
- AutoGrip™ automatic cord grip clamps cord during assembly and reduces wiring time.
- Back wired Dead-Front construction with easy wire clamp type terminals.
- Tapered cord grip cover eliminates cord snags.
- High strength thermoplastic connector resists breakage in high abuse locations.
- Terminals accept #12AWG-#4AWG conductors.
- Thermoplastics suitable for 85°C/185°F continuous use.

AutoGrip™ Plugs, Connectors and Flanged Inlets

Rating A	V/AC	NEMA	Description	Cord Diameter	Color	Plug	Catalog No. Connector	Flanged Inlet
30	125/250	10-30	Straight	0.425-1.310 (10.80-33.27mm)	Gray	9337N	9341N	9337NFI
			Angle	0.560-1.310 (14.22-33.27mm)	Gray	9352AN	–	–
50	125/250	10-50	Straight	0.425-1.30 (10.80-33.27mm)	Gray	4524N	4526N	4524NFI
			Angle	0.560-1.30 (14.22-33.27mm)	Gray	7952AN		



Commercial Specification Grade Range and Dryer Plugs – for Replacement Use Only

FEATURES

- Dual current model furnished with blades for 30 and 50 amp applications
- Terminals have pressure plates to protect wires.
- Model 80 made from abuse resistant thermoplastic.

Standard Grade Power Plugs and Receptacles

Rating A	V/AC	NEMA	Cord Description	Diameter	Color	Plug	Matching Receptacle
30/50	125/250	10-30/10-50	Angle Universal Vinyl	0.800" (20.32mm)	Black	80	125BK*† 38B 122B 112BK* 32B*

* Not CSA certified
† Not NOM



10-30P



10-30R



10-50P



10-50R