


Industrial grade 15A locking devices

Product description

2-pole, 3-wire grounding
15A, 125V/AC
NEMA L5-15



CWL515C



CWL515PAN



4721N

Industrial grade plugs & connectors



| Rating A | V/AC | NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|-------|---------------------------|----------------------------|--------|------------------------------------|------------------------------------|--|--|
| 15 | 125 | L5-15 | Safety grip straight body | 0.33-0.66" (8.4-16.7mm) | BK & W | <input type="checkbox"/> CWL515P | <input type="checkbox"/> CWL515C | | |
| | | | Safety grip angled body | 0.33-0.66" (8.4-16.7mm) | BK & W | <input type="checkbox"/> CWL515PAN | <input type="checkbox"/> CWL515CAN | | |
| | | | Auto grip | 0.33-0.66" (8.4-16.7mm) | BK & W | <input type="checkbox"/> 4721N | <input type="checkbox"/> 4731N | | |

Industrial grade receptacles



| Rating A | V/AC | NEMA | Description | Color | Single receptacle | Duplex receptacle | | |
|-------------|------|-------|--------------------------------------|-------|-----------------------------------|----------------------------------|--|--|
| 15 | 125 | L5-15 | Standard industrial | BK | <input type="checkbox"/> CWL515R* | — | | |
| | | | Standard industrial | BK | — | <input type="checkbox"/> 4700 | | |
| | | | Isolated ground | RN | <input type="checkbox"/> IGL515R* | <input type="checkbox"/> IG4700* | | |
| | | 5-15 | Combination locking & straight blade | BK | — | <input type="checkbox"/> 5792* | | |

*Not Fed Spec

Industrial grade flanged inlet



| Rating A | V/AC | NEMA | Description | Color | Flanged inlet | | |
|-------------|------|-------|---------------------|--------|-----------------------------------|--|--|
| 15 | 125 | L5-15 | Standard industrial | BK & W | <input type="checkbox"/> CWL515FI | | |

Industrial grade flanged outlet



| Rating A | V/AC | NEMA | Description | Color | Flanged outlet | | |
|-------------|------|-------|---------------------|--------|-----------------------------------|--|--|
| 15 | 125 | L5-15 | Standard industrial | BK & W | <input type="checkbox"/> CWL515FO | | |

Dimensional information:
C-76-C-78

Plug & connector specification information:
L5-15: C-84

Receptacle specification information:
L5-15: C-86

Isolated ground L5-15: C-86

Flanged inlet & flanged outlet specification information:
L5-15: C-88

Color information:

BK (Black), RN (Orange), W (White)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32