

# EF EXTRA FLEXIBLE CONDUIT

## LFMC SEALTITE® EF EXTRA FLEXIBLE CONDUIT



### DESCRIPTION:

- Flexible metal core liquid tight conduit
- Designed for applications where no approvals are required
- Also available in black by special order
- Uses standard liquid tight connectors for easy installation
- Additional Put-ups available

### SPECIFICATIONS:

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray or Black
- Temp. range: -4°F to +176°F (-20°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

### APPLICATIONS:

- Applications where no approvals are required

See: [www.naed.org](http://www.naed.org) [www.nema.org](http://www.nema.org)  
[www.anacondasealtite.com](http://www.anacondasealtite.com)



Square-Locked Design  
3/8" - 2"



| Trade Size (mm) | Item ID | Std. Pkg. (feet) | Inside Diameter (inches) |       | Outside Diameter (inches) |       | Bend Radius (inches) | Weight (lbs/100 ft) |
|-----------------|---------|------------------|--------------------------|-------|---------------------------|-------|----------------------|---------------------|
|                 |         |                  | Min                      | Max   | Min                       | Max   |                      |                     |
| 3/8" (12)       | 39402   | 100              | 0.485                    | 0.505 | 0.690                     | 0.710 | 2.0                  | 21                  |
|                 | 39404   | 800              |                          |       |                           |       |                      |                     |
| 1/2" (16)       | 39412   | 100              | 0.620                    | 0.640 | 0.820                     | 0.840 | 2.5                  | 25                  |
|                 | 39413   | 1000             |                          |       |                           |       |                      |                     |
|                 | 39414   | 500              |                          |       |                           |       |                      |                     |
| 3/4" (21)       | 39422   | 100              | 0.815                    | 0.835 | 1.030                     | 1.050 | 3.0                  | 39                  |
|                 | 39428   | 500              |                          |       |                           |       |                      |                     |
|                 | 39429   | 1000             |                          |       |                           |       |                      |                     |
| 1" (27)         | 39431   | 100              | 1.030                    | 1.055 | 1.290                     | 1.315 | 4.0                  | 51                  |
|                 | 39438   | 400              |                          |       |                           |       |                      |                     |
| 1-1/4" (35)     | 39441   | 50               | 1.370                    | 1.395 | 1.635                     | 1.660 | 4.5                  | 66                  |
|                 | 39448   | 250              |                          |       |                           |       |                      |                     |
| 1-1/2" (41)     | 39451   | 50               | 1.575                    | 1.600 | 1.865                     | 1.900 | 5.5                  | 104                 |
|                 | 39454   | 150              |                          |       |                           |       |                      |                     |
| 2" (53)         | 39461   | 50               | 2.020                    | 2.045 | 2.340                     | 2.375 | 7.0                  | 136                 |
|                 | 39468   | 100              |                          |       |                           |       |                      |                     |

FITTINGS FINDER



IP 66/67 with approved fittings

