

# DEWALT®

ENGINEERED BY Powers™

## Rod Hanging System for Concrete, Wood & Steel



## Hangermate®+

# DEWALT®

ENGINEERED BY Powers™



UL & FM FULL LISTING  
PAGES 10-11

### THREAD PROFILE


low torque,  
fast installation,  
full concrete  
engagement

### STANDARD 1/4" BIT

no need for  
specialty bit for  
installation

### HARDENED STEEL

installs in hard  
concrete and  
remains ductile



**THREADED ROD**  
available in 1/4"  
or 3/8" rod sizes

**EXTERNAL  
3/8" THREAD**  
for attaching  
directly to  
anchor



	DEWALT Hangermate+	ITW Buildex Sammys®
Approved Embedments	1-5/8" & 2-1/2"	2-1/4"
Bit Size	1/4" ANSI	Specialty
Pullout, N <sub>p,cr</sub> *	1412 lbs	857 lbs

\* for 2-1/2" embedment

Sammys® is a registered trademark of Illinois Tool Works Inc.

## Faster Installation

Hangermate+ VS Drop-In Anchor\*\*

**25%**  
Faster Installation

DEWALT  
Hangermate+  
for Concrete

Traditional  
Drop-in  
Anchor

\*\* 1/4"x1-5/8" concrete screw (with 3/8" coupler head) versus  
3/8" Drop-In anchor

### Installation Driver and Bit Reference

CAT #	DESCRIPTION	DRIVER	BIT
<b>Hangermate+ Concrete - Internally Threaded</b>			
PFM2211100	1/4" x 1-5/8"	PFM1491050	DW5517
PFM2211200	1/4" x 1-5/8"	PFM1491100	DW5517
PFM2211250	1/4" x 2-1/2"	PFM1491100	DW5517
<b>Hangermate+ For Concrete - Externally Threaded</b>			
PFM1421000	1/4" x 1-5/8"	DW22862	DW5517
PFM1421050	1/4" x 2-1/2"	DW22862	DW5517
<b>Pivot For Concrete - Angled Applications</b>			
PFM2281300	1/4 x 2"	PFM2201250	02796SD
<b>Suspender For Concrete - Dual-Directional</b>			
PFM2271050	5/16" x 2-1/4"	PFM2201300	DW5517



# Hangermate®+

## Rod Hanging Anchors for Concrete

	CAT #	DESCRIPTION	SAMMYS® MODEL #	HANG	ROD SIZE	QTY	MSTR
<b>Hangermate+ For Concrete - Internally Threaded</b>							
	PFM2211100	1/4" x 1-5/8"	CST 200	Vertical	1/4"	25	125
	PFM2211200	1/4" x 1-5/8"	CST 20	Vertical	3/8"	25	125
	PFM2211250	1/4" x 2-1/2"	CCST 516	Vertical	3/8"	25	125
<b>Hangermate+ For Concrete - Externally Threaded</b>							
	PFM1421000	1/4" x 1-5/8"	-	Vertical	3/8"	25	125
	PFM1421050	1/4" x 2-1/2"	-	Vertical	3/8"	25	125
<b>Hangermate+ Pivot For Concrete - Angled Applications</b>							
	PFM228130	1/4 x 2"	SH-GST/CST 20	Variable	3/8"	25	125
<b>Hangermate+ Suspender For Concrete - Dual-Directional</b>							
	PFM2271050	5/16" x 2-1/4"	-	Vert. & Hori.	3/8"	25	125

### The Complete Anchoring Solution - Installation Accessories and Tools

	CAT #	DESCRIPTION	HANGERMATE+	QTY	MSTR QTY
	PFM1491050	1/4" Socket Driver	Concrete Rod Hanger	1	5
	PFM1491100	3/8" Socket Driver	Concrete Rod Hanger	1	5
	DW22862	1/2" Drive Socket	Externally Threaded Concrete Rod Hanger	1	-
	PFM2201300	Suspender Driver	Suspender	1	5
	PFM2201250	Pivot Driver	Pivot	1	5
	DWMT73934B	1/2" Impact Rated® Deep Socket	External	1	-
	DW2547IR	1/4" Hex to 1/2" Square Adapter			
	DW5517	1/4" X 6" (4" usable length) SDS+ Full Head Carbide Masonry Drill Bit			
	02796SD	Hex Shank SDS-Plus (only for Pivot for Concrete)			
	PFM2201050	Adapter for hanging 1/2" rod (3/8" to 1/2" Adapter)			
	DCH273P2DH	20V MAX* Brushless Rotary Hammer			
	DCF887D2	20V MAX* XR Brushless 3-Speed Impact Driver			
	DCF883M2	20V MAX* Lithium Ion 3/8" Impact Wrench			
	DCS350D1	Cordless Threaded Rod Cutter			

\* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

# DEWALT®

ENGINEERED BY **Powers™**



UL & FM FULL LISTING  
PAGES 10-11



**TYPE 17 GIMLET**  
easy material  
removal, no  
pre-drilling  
required

**SINGLE PIECE  
DESIGN†**  
allows removal  
and adjustment

† Available on PFM2251000,  
PFM2251100 & PFM2261100



**SIDE MOUNT  
OPTION**  
for horizontal  
applications



**WOOD DRIVER**  
spin off feature helps  
reduce over driving



	DEWALT Hangermate	ITW Buildex Sammys®
Dual Head	Suspender	No
Point Style	Type 17 Gimlet	Gimlet Only
Single Piece Design	Select Sizes	All 2-piece

## Type 17 Gimlet Helps Reduce Splitting\*

\*Compared to Sammys® drilled 2" into pressure treated lumber with DEWALT DCD790D2

DEWALT  
1/4" x 2"



Sammys®  
1/4" x 2"








Sammys® is a registered trademark of Illinois Tool Works Inc.

### Installation Driver Reference

CAT #	DESCRIPTION	DRIVER
<b>Hangermate Wood - Vertical</b>		
PFM2251000	1/4" x 2"	PFM2201150
PFM2251050	1/4" x 1"	PFM2201150
PFM2251100	1/4" x 2"	PFM2201150
PFM2251150	5/16" x 2-1/2"	PFM2201150
PFM2251200	1/4" x 3"	PFM2201150
PFM2251250	1/4" x 4"	PFM2201150
PFM2251300	5/16" x 2-1/2"	PFM2201150
<b>Hangermate Wood - Horizontal</b>		
PFM2261000	1/4" x 1"	PFM2201150
PFM2261050	1/4" x 1"	PFM2201150
PFM2261100	1/4" x 2"	PFM2201150
PFM2261150	5/16" x 2-1/2"	PFM2201150
<b>Pivot For Wood - Angled Applications</b>		
PFM2281100	1/4" x 2"	PFM2201250
<b>Suspender For Wood - Dual-Directional</b>		
PFM2271000	5/16" x 2-1/4"	PFM2201300
<b>Wood - Acoustical Ceiling Screw Eyelet</b>		
PFM2251500	1/4" x 3"	PFM2201350

# Hangermate®

## Rod Hanging Anchors for Wood

	CAT #	DESCRIPTION	SAMMYS® MODEL #	HANG	ROD SIZE	QTY	MSTR QTY
<b>Hangermate For Wood - Vertical</b>							
	PFM2251000	1/4" x 2"	GST 200	Vertical	1/4"	25	125
	PFM2251050	1/4" x 1"	GST 10	Vertical	3/8"	25	125
	PFM2251100	1/4" x 2"	GST 20	Vertical	3/8"	25	125
	PFM2251150	5/16" x 2-1/2"	GST 25-380	Vertical	3/8"	25	125
	PFM2251200	1/4" x 3"	GST 30	Vertical	3/8"	25	125
	PFM2251250	1/4" x 4"	-	Vertical	3/8"	25	125
	PFM2251300	5/16" x 2-1/2"	GST 2	Vertical	1/2"	25	125
<b>Hangermate For Wood - Horizontal</b>							
	PFM2261000	1/4" x 1"	SWG 200	Horizontal	1/4"	25	125
	PFM2261050	1/4" x 1"	SWG 10	Horizontal	3/8"	25	125
	PFM2261100	1/4" x 2"	SWG 20	Horizontal	3/8"	25	125
	PFM2261150	5/16" x 2-1/2"	SWG 25-380	Horizontal	3/8"	25	125
<b>Hangermate Pivot For Wood - Angled Applications</b>							
	PFM2281100	1/4" x 2"	SH-GST 20	Variable	3/8"	25	125
<b>Hangermate Suspender For Wood - Dual-Directional</b>							
	PFM2271000	5/16" x 2-1/4"	-	Vertical & Horizontal	3/8"	25	125
<b>Hangermate For Wood - Acoustical Ceiling Screw Eyelet</b>							
	PFM2251500	3/16" x 3"	CWSD 15	Vertical & Horizontal	Eyelet Hole 3/16"	25	125

### The Complete Anchoring Solution - Installation Accessories and Tools

	CAT #	DESCRIPTION	HANGERMATE	QTY	MSTR QTY
	PFM2201150	Wood Socket Driver	Rod Hanger	1	5
	PFM2201300	Suspender Driver	Suspender	1	5
	PFM2201250	Pivot Driver	Pivot	1	5
	PFM2201350	Ceiling Screw Eyelet Driver	Acoustical	1	5
	PFM2201100	Pole Tool Kit	Rod Hanger	1	5
	DCF6102S2	12V Max* Lithium Ion 1/4" (13mm) Screwdriver Kit			
	DCD790D2	20V MAX* XR Lithium Ion Brushless Compact Drill/Driver Kit			
	DCD990M2	20V MAX* XR Lithium Ion Premium 3-Speed Drill/Driver Kit			
	DCD995M2	20V MAX* XR Lithium Ion Brushless Premium Hammerdrill Kit			



\* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

# DEWALT®

ENGINEERED BY Powers™



UL & FM FULL LISTING  
PAGES 10-11



**HORIZONTAL MOUNT OPTION**








	DEWALT Hangermate	ITW Buildex Sammys®
Dual Head	Suspender	No
Single Piece Design	Yes	All 2-piece
UL Approved Range*	12 SKUs	8 SKUs

\*On select sizes with coupling nut  
Sammys is a registered trademark of Illinois Tool Works Inc.

### Installation Driver Reference

CAT #	DESCRIPTION	DRIVER
<b>Hangermate Steel - Vertical</b>		
PFM2231000	1/4-20 1" #3	PFM2201200
PFM2231100	1/4-20 x 1" #3	PFM2201200
PFM223110N	1/4-20 x 1" #3 / nut	PFM2201200
PFM2231150	1/4"-20 x 1-1/2" #5	PFM2201200
PFM223115N	1/4-20 x 1-1/2" #5 / nut	PFM2201200
PFM2231200	1/4-20 x 1-1/2" #3	PFM2201200
PFM223120N	1/4-20x1-1/2" #3 / nut	PFM2201200
PFM2231250	1/4-20 x 2" #3	PFM2201200
<b>Hangermate Steel - Horizontal</b>		
PFM2241100	1/4-20 x 1" #3	PFM2201200
PFM224110N	1/4-20 x 1" #3 / nut	PFM2201200
PFM2241150	1/4-20 x 1-1/2" #3	PFM2201200
PFM224115N	1/4-20 x 1-1/2" #3 / nut	PFM2201200
PFM2241200	1/4-20 x 1-1/2" #5	PFM2201200
PFM224120N	1/4-20 x 1-1/2" #5 /nut	PFM2201200
<b>Pivot Steel - Angled Applications</b>		
PFM2281150	1/4-20 x 1" #3	PFM2201250
PFM2281200	12-20 x 1-3/4" #5	PFM2201250
PFM2281250	1/4-14 x 1" #3	PFM2201250
<b>Suspender Steel - Dual-Directional</b>		
PFM227110N	1/4-20 x 1" #3 / nut	PFM2201300
PFM227120N	1/4-20 x 1-1/2" #3 / nut	PFM2201300
PFM227130N	1/4-20 x 1-1/2" #5 / nut	PFM2201300
<b>Steel - Acoustical Ceiling Screw Eyelet</b>		
PFM2231500	1/4" x 3"	PFM2201350
PFM2231550	1/4" x 3-1/4"	PFM2201350

# Hangermate® Rod Hanging Anchors for Steel

	CAT #	DESCRIPTION	SAMMYS® MODEL #	HANG	ROD SIZE	QTY	MSTR QTY
<b>Hangermate For Steel - Vertical</b>							
	PFM2231000	1/4-20 x 1" #3	DSTR 100	Vertical	1/4"	25	125
	PFM2231100	1/4-20 x 1" #3	-	Vertical	3/8"	25	125
	PFM223110N	1/4-20 x 1" #3 / nut	DSTR 1	Vertical	3/8"	25	125
	PFM2231150	1/4"-20 x 1-1/2" #5	DSTR 1-1/2	Vertical	3/8"	25	125
	PFM223115N	1/4-20 x 1-1/2" #5 / nut	DSTR 1	Vertical	3/8"	25	125
	PFM2231200	1/4-20 x 1-1/2" #3	-	Vertical	3/8"	25	125
	PFM223120N	1/4-20x1-1/2" #3 / nut	DST15	Vertical	3/8"	25	125
	PFM2231250	1/4-20 x 2" #3	DST 20	Vertical	3/8"	25	125
<b>Hangermate For Steel - Horizontal</b>							
	PFM2241100	1/4-20 x 1" #3	SDW 10	Horizontal	3/8"	25	125
	PFM224110N	1/4-20 x 1" #3 / nut	SDWR 1	Horizontal	3/8"	25	125
	PFM2241150	1/4-20 x 1-1/2" #3	-	Horizontal	3/8"	25	125
	PFM224115N	1/4-20 x 1-1/2" #3 / nut	-	Horizontal	3/8"	25	125
	PFM2241200	1/4-20 x 1-1/2" #5	SWT 15	Horizontal	3/8"	25	125
	PFM224120N	1/4-20 x 1-1/2" #5 /nut	SWDR 1-1/2	Horizontal	3/8"	25	125
<b>Hangermate Pivot For Steel - Angled Applications</b>							
	PFM2281150	1/4-20 x 1" #3	SH-DSTR 1	Variable	3/8"	25	125
	PFM2281200	12-20 x 1-3/4" #5	SH-TEK 50	Variable	3/8"	25	125
	PFM2281250	1/4-14 x 1" #3	-	Variable	3/8"	25	125
<b>Hangermate Suspender For Steel - Dual-Directional</b>							
	PFM227110N	1/4-20 x 1" #3 / nut	-	Vert. & Horz.	3/8"	25	125
	PFM227120N	1/4-20 x 1-1/2" #3 / nut	-	Vert. & Horz.	3/8"	25	125
	PFM227130N	1/4-20 x 1-1/2" #5 / nut	-	Vert. & Horz.	3/8"	25	125
<b>Hangermate For Steel - Acoustical Ceiling Screw Eyelet</b>							
	PFM2231500	3/16" x 2"	CWSD 1	Vert. & Horz.	Eyelet Hole 3/16"	25	125
	PFM2231550	3/16" x 3-1/4"	CWSD 2	Vert. & Horz.		25	125

Recommended 1300 to 2000 rpms for proper installation.

## The Complete Anchoring Solution - Installation Accessories and Tools

	CAT #	DESCRIPTION	HANGERMATE	QTY	MSTR QTY
	PFM2201200	Steel Socket (Silver)	Rod Hanger	1	5
	PFM2201300	Suspender Driver	Suspender	1	5
	PFM2201250	Pivot Driver	Pivot	1	5
	PFM2201350	Ceiling Screw Eyelet Driver	Acoustical	1	5
	PFM2201100	Pole Tool Kit	Rod Hanger	1	5
	PFM2201050	Adapter for hanging 1/2" rod (3/8" to 1/2" Adapter)			
	DCD991P2	20 V MAX* XR Lithium Ion Brushless 3-Speed Drill / Driver Kit			
	DCF887D2	20V MAX* XR 1/4" 3-Speed Impact Driver Kit			

\* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

# DEWALT®

ENGINEERED BY Powers™

## Pivot™

**THREADS**  
designed for  
concrete

**HARDENED STEEL**  
specially engineered  
and designed to cut  
through hard materials

**ROTATIONAL  
HEAD**  
almost 90 degrees  
of rotation for  
flexible positioning

**THREADS**  
designed  
for wood

**THREADS**  
designed  
for steel



### Pivot Installation Driver & Bit Reference

NUMBER	DESCRIPTION	DRIVER	DRILL BIT
<b>Pivot For Concrete</b>			
PFM2281300	1/4 x 2"	PFM2201250	02796SD
<b>Pivot For Wood</b>			
PFM2281100	1/4" x 2"	PFM2201250	*
<b>Pivot For Steel</b>			
PFM2281150	1/4-20 x 1" #3	PFM2201250	*
PFM2281200	12-20 x 1-3/4" #5	PFM2201250	*
PFM2281250	1/4-14 x 1" #3	PFM2201250	*

\* No pre-drilling necessary

◀ **STAR DRIVE T-25**  
full engagement  
driving through  
tough materials







# Hangermate® Specialty Rod Hanging Anchors

## Suspender™



UL & FM FULL LISTING  
PAGES 10-11  
APPROVED

**MULTIPLE  
THREADS**  
different thread  
and point styles


**TWIN LEAD  
THREAD**  
for thread  
engagement  
(concrete &  
wood)

**DUAL DIRECTIONAL  
THREAD**  
one part for vertical or  
horizontal application

### Suspender Installation Driver & Bit Reference

NUMBER	DESCRIPTION	DRIVER	DRILL BIT
<b>Suspender For Concrete</b>			
PFM2271050	5/16" x 2-1/4"	PFM2201300	DW5517
<b>Suspender For Wood</b>			
PFM2271000	5/16" x 2-1/4"	PFM2201300	*
<b>Suspender For Steel</b>			
PFM227110N	1/4-20 x 1" #3/nut	PFM2201300	*
PFM227120N	12-20 x 1-1/2" #3/nut	PFM2201300	*
PFM227130N	1/4-14 x 1" #5/nut	PFM2201300	*

\* No pre-drilling necessary



# DEWALT®

ENGINEERED BY **POWERS™**

## APPROVALS



### Hangermate+ For Concrete - Internally Threaded

CAT #	DESCRIPTION	HANG	ROD SIZE	DRIVER	ULTIMATE TENSILE LOAD (LBS)*	PIPE SIZE	LOAD	PIPE SIZE	LOAD	ICC-ES
PFM2211100	1/4" x 1-5/8"	Vertical	1/4"	PFM1491050	2,835	-	-	4"	1,475	ESR-3889
PFM2211200	1/4" x 1-5/8"	Vertical	3/8"	PFM1491100	2,835	-	-	4"	1,475	ESR-3889
PFM2211250	1/4" x 2-1/2"	Vertical	3/8"	PFM1491100	3,650	-	-	4"	1,475	ESR-3889

\*In 2,500psi uncracked concrete

### Hangermate+ For Concrete - Externally Threaded

PFM1421000	1/4" x 1-5/8"	Vertical	3/8"	DW22862	2,835	-	-	4"	1,475	ESR-3889
PFM1421050	1/4" x 2-1/2"	Vertical	3/8"	DW22862	3,650	-	-	4"	1,475	ESR-3889

\*In 2,500psi uncracked concrete

### Hangermate+ Pivot For Concrete - Angled Applications

PFM2281300	1/4 x 2"	Variable	3/8"	PFM2201250	2,830 (Vert.)	-	-	-	-	-
					990 (45°)	-	-	-	-	-

\* In 2,500psi uncracked concrete

### Hangermate+ Suspender For Concrete - Dual-Directional

PFM2271050	5/16" x 2-1/4"	Vert. & Hori.	3/8"	PFM2201300	2,188 (Vert.)	-	-	4"	1,475	-
					2,767 (Horz.)	-	-	4"	1,475	-

\*In 3,650psi uncracked concrete

### Hangermate+ For Wood - Vertical

PFM2251000	1/4" x 2"	Vertical	1/4"	PFM2201150	1,510	-	-	-	-	-
PFM2251050	1/4" x 1"	Vertical	3/8"	PFM2201150	685	-	-	-	-	-
PFM2251100	1/4" x 2"	Vertical	3/8"	PFM2201150	1,510	3"	1,050	-	-	-
PFM2251150	5/16" x 2-1/2"	Vertical	3/8"	PFM2201150	2,670	4"	1,500	4"	1,475	-
PFM2251200	1/4" x 3"	Vertical	3/8"	PFM2201150	2,075	3"	1,050	-	-	-
PFM2251250	1/4" x 4"	Vertical	3/8"	PFM2201150	2,075	3"	1,050	-	-	-
PFM2251300	15/16" x 2-1/2"	Vertical	1/2"	PFM2201150	2,670	-	-	-	-	-

\*Ultimate Loads In Douglas Fir

### Hangermate+ For Wood - Horizontal

PFM2261000	1/4" x 1"	Horizontal	1/4"	PFM2201150	685	-	-	-	-	-
PFM2261050	1/4" x 1"	Horizontal	3/8"	PFM2201150	685	-	-	-	-	-
PFM2261100	1/4" x 2"	Horizontal	3/8"	PFM2201150	1,800	3"	1,050	-	-	-
PFM2261150	5/16" x 2-1/2"	Horizontal	3/8"	PFM2201150	1,450	3"	1,050	-	-	-

\*Ultimate Loads In Douglas Fir

### Hangermate+ Pivot For Wood - Angled Applications

PFM2281100	1/4" x 2"	Variable	3/8"	PFM2201250	1,470 (Vert.)	-	-	-	-	-
					1,154 (45°)	-	-	-	-	-

\*Ultimate Loads In Douglas Fir

### Hangermate+ Suspender For Wood - Dual-Directional

PFM2271000	5/16" x 2-1/4"	Vert. & Horz.	3/8"	PFM2201300	2,487	-	-	4"	1,475	-
------------	----------------	---------------	------	------------	-------	---	---	----	-------	---

\*Ultimate Loads In Douglas Fir      FM Load applies to vertical only

### Hangermate+ For Wood - Acoustical Ceiling Screw Eyelet

PFM2251500	3/16" x 3"	Vert. & Horz.	3/16"	PFM2201350	883	-	-	-	-	-
------------	------------	---------------	-------	------------	-----	---	---	---	---	---

\*Ultimate Loads In Douglas Fir

# Hangermate®

## Rod Hanging Anchor Approvals

### APPROVALS



#### Hangermate+ For Steel - Vertical

CAT #	DESCRIPTION	HANG	ROD SIZE	DRIVER	MIN. THICK.	MAX. THICK.	ULTIMATE TENSILE LOAD (MATERIAL THICKNESS)	LOAD DIRECTION	PIPE SIZE	UL THICK.	PIPE SIZE	FM THICK.
PFM2231000	1/4-20 1" #3	Vert.	1/4"	PFM2201200	0.060	0.250	2,375 (0.125")	-	-	-	-	-
PFM2231100	1/4-20 x 1" #3	Vert.	3/8"	PFM2201200	0.060	0.250	2,375 (0.125")	V	4"	0.060"	-	-
PFM223110N	1/4-20 x 1" #3/nut	Vert.	3/8"	PFM2201200	0.060	0.250	4,690 (0.125")	V	4"	0.125"	4"	12 ga.
PFM2231150	1/4"-20 x 1-1/2" #5	Vert.	3/8"	PFM2201200	0.188	0.250	3,675 (0.188")	V	4"	0.060"	4"	16 ga.
PFM223115N	1/4-20 x 1-1/2" #5/nut	Vert.	3/8"	PFM2201200	0.060	0.250	5,810 (0.188")	V	4"	0.125"	4"	12 ga.
PFM2231200	1/4-20 x 1-1/2" #3	Vert.	3/8"	PFM2201200	0.188	0.250	2,375 (0.125")	V	4"	0.060"	-	-
PFM223120N	1/4-20 x 1-1/2" #3/nut	Vert.	3/8"	PFM2201200	0.060	0.250	4,690 (0.125")	V	4"	0.060"	-	-
PFM2231250	1/4-20 x 2" #3	Vert.	3/8"	PFM2201200	0.060	0.250	2,375 (0.125")	V	4"	0.125"	-	-

#### Hangermate+ For Steel - Horizontal

PFM2241100	1/4-20 x 1" #3	Horiz.	3/8"	PFM2201200	0.060	0.250	2,570 (0.111")	H	-	-	-	-
PFM224110N	1/4-20 x 1" # /nut	Horiz.	3/8"	PFM2201200	0.060	0.250	2,810 (0.111")	H	4"	0.060"	4"	16 ga.
PFM2241150	1/4-20 x 1-1/2" #3	Horiz.	3/8"	PFM2201200	0.060	0.250	2,570 (0.111")	H	-	-	-	-
PFM224115N	1/4-20 x 1-1/2" #3/nut	Horiz.	3/8"	PFM2201200	0.060	0.250	2,810 (0.111")	H	4"	0.060"	4"	16 ga.
PFM2241200	1/4-20 x 1-1/2" #5	Horiz.	3/8"	PFM2201200	0.060	0.500	3,530 (0.188")	H	-	-	-	-
PFM224120N	1/4-20 x 1-1/2" #5/nut	Horiz.	3/8"	PFM2201200	0.060	0.500	2,810 (0.111")	H	4"	0.060"	4"	16 ga.

#### Hangermate+ Pivot For Steel - Angled Applications

PFM2281150	1/4-20 x 1" #3	Variable	3/8"	PFM2201250	0.060	0.188	3,210 (0.188")	V	-	-	-	-
							975 (0.188")	45°	-	-	-	-
PFM2281200	12-20 x 1-3/4" #5	Variable	3/8"	PFM2201250	0.11	0.188	3,270 (0.188")	V	-	-	-	-
							975 (0.188")	45°	-	-	-	-
PFM2281250	1/4-14 x 1" #3	Variable	3/8"	PFM2201250	0.188	0.5	2,875 (0.188")	V	-	-	-	-
							875 (0.188")	45°	-	-	-	-

#### Hangermate+ Suspender For Steel - Dual-Directional

PFM227110N	1/4-20 x 1" #3/nut	Vert. & Horiz.	3/8"	PFM2201300	0.060	0.210	4,690 (0.125")	V	4"	0.060"	4"	16 ga.
								H	4"	0.060"	4"	16 ga.
PFM227120N	1/4-20 x 1-1/2" #3/nut	Vert. & Horiz.	3/8"	PFM2201300	0.060	0.210	4,690 (0.125")	V	4"	0.060"	4"	16 ga.
								H	4"	0.060"	4"	16 ga.
PFM227130N	1/4-20 x 1-1/2" # nut	Vert. & Horiz.	3/8"	PFM2201300	0.188	0.500	4,690 (0.125")	V	4"	0.060"	4"	16 ga.
								H	4"	0.060"	4"	16 ga.

#### Hangermate+ For Steel - Acoustical Ceiling Screw Eyelet
































































PFM2251500	3/16" x 2"	3/16"	PFM2201350	-	0.060	590 (0.188")	-	-	-	-	-
PFM2251550	3/16" x 3-1/4"	3/16"	PFM2201350	-	0.060	590 (0.188")	-	-	-	-	-























































































Loads vary depending on steel thickness.  
Contact DEWALT for more information.

# DEWALT®

ENGINEERED BY **POWERS™**

## Hangermate®+ Rod Hanging Anchors

DeWALT LOCATIONS		Field Service	DeWALT Tool Service	Anchor Distribution Center
ALABAMA	Birmingham	205-942-0538		
	Mobile	251-602-1000		
ALASKA	Anchorage	907-561-7181		
ARKANSAS	Little Rock	501-372-3040		
ARIZONA	Phoenix	602-437-1200		
	Phoenix	602-431-8024		
CALIFORNIA	San Francisco	510-783-3959		
	Hayward	510-293-1500		
	San Diego	858-279-2011		
	Anaheim	714-414-0369		
	Sacramento	916-344-3520		
	Ontario	909-930-1437		
COLORADO	Denver	303-922-8325		
	Denver	303-922-9202		
CONNECTICUT	Hartford	860-563-5800		
FLORIDA	Fl. Lauderdale	954-321-6635		
	Tampa	813-884-0434		
	Orlando	407-657-0474		
	Orlando	813-626-4500		
GEORGIA	Atlanta	770-246-1710		
	Atlanta	678-966-0000		
HAWAII	Honolulu	808-842-9925		
IOWA	Des Moines	515-270-1340		
ILLINOIS	Addison	630-521-1097		
	Addison	630-960-3156		
INDIANA	Indianapolis	317-243-8308		
	Indianapolis	317-773-1668		
KANSAS	Kansas City	913-495-4330		
	Kansas City	816-472-5033		
	Wichita	316-943-1271		
KENTUCKY	Louisville	502-380-3748		
LOUISIANA	New Orleans	504-832-2187		
	Baton Rouge	225-296-3191		
MARYLAND	Baltimore	410-536-0722		
	Capital Heights	301-333-0865		
	Baltimore / DC	301-773-1722		
MASSACHUSETTS	Boston	781-329-3407		
MICHIGAN	Grand Rapids	616-261-0425		
	Detroit	248-597-5000		
	Detroit	248-543-8600		
MINNESOTA	Minneapolis	952-884-9191		
	Minneapolis	612-331-3770		
MISSOURI	St. Louis	314-997-9100		
	Kansas City	816-472-5033		
NEVADA	Las Vegas	702-889-6025		
NEW JERSEY	Elmwood Park	201-475-3524		

DeWALT LOCATIONS		Field Service	DeWALT Tool Service	Anchor Distribution Center
NEW MEXICO	Albuquerque	505-884-1002		
NEW YORK	Buffalo	716-884-6220		
	Queens	718-335-1042		
	Rochester	585-228-2080		
	Long Island	631-952-2008		
	Albany	518-785-1867		
	New York	800-524-3244		
NORTH CAROLINA	Charlotte	704-392-0245		
	Charlotte	704-375-5012		
	Greensboro	336-852-1300		
	Raleigh	919-878-0357		
OHIO	Cleveland	440-842-9100		
	Cincinnati	513-772-3111		
	Columbus	614-895-3112		
OKLAHOMA	Oklahoma City	405-634-8403		
	Tulsa	918-249-8641		
OREGON	Portland	503-255-6556		
PENNSYLVANIA	Philadelphia	215-271-5500		
	Pittsburgh	412-642-0204		
	Allentown	610-435-9544		
	York	717-755-3441		
SOUTH CAROLINA	Charleston	843-745-9197		
	Greenville	864-299-8662		
TENNESSEE	Memphis	901-384-8100		
	Nashville	615-242-1633		
	Nashville	615-248-2667		
	Knoxville	865-688-0921		
TEXAS	Dallas	972-446-2996		
	Dallas	972-446-5985		
	Houston	713-466-1194		
	Houston	281-491-0351		
	San Antonio	210-732-1221		
	Fort Worth	817-831-3828		
UTAH	Austin	512-382-3971		
	Salt Lake City	801-486-5828		
VIRGINIA	Salt Lake City	801-466-9428		
	Virginia Beach	757-363-0091		
WASHINGTON	Seattle	206-763-2010		
	Spokane	509-535-9252		
	Seattle	425-251-0312		
WEST VIRGINIA	Charleston	304-343-0289		
WISCONSIN	Milwaukee	414-645-4285		
	Milwaukee	414-645-8821		

DeWALT, ELCO, & POWERS Anchors and Fasteners Inquiries: 800-524-3244

DeWALT, ELCO, & POWERS Anchors and Fasteners Technical Questions: email: [anchors@dewalt.com](mailto:anchors@dewalt.com)

Dealer Stamp

# 1-800-4 DEWALT®

[www.DEWALT.com](http://www.DEWALT.com)

Copyright © 2018 DEWALT. The yellow/black color scheme is a trademark for DEWALT power tools, accessories, anchors & concrete adhesives.

ICDWHGRMBR\_r.4 1/18