



Industrial grade straight blade devices

Product description

2-pole, 3-wire grounding
15A, 125V/AC
NEMA 5-15



AH5266



AH5969BK



AH5278C



AH5278

Industrial grade plugs & connectors



| Rating A | V/AC | NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|------|--------------------------|----------------------------|--------|-----------------------------------|-----------------------------------|---|---|
| 15 | 125 | 5-15 | Ultra grip straight body | 0.33-0.66" (8.3-16.7mm) | BK & W | <input type="checkbox"/> AH5266 | <input type="checkbox"/> AH5269 | • | • |
| | | | Ultra grip straight body | 0.33-0.66" (8.3-16.7mm) | BK | <input type="checkbox"/> AH5266BK | <input type="checkbox"/> AH5269BK | • | • |
| | | | Safety grip angled body | 0.33-0.66" (8.3-16.7mm) | BK & W | <input type="checkbox"/> AH5266A | — | • | • |
| | | | Quick grip straight body | 0.22-0.66" (5.6-16.7mm) | BK | <input type="checkbox"/> AH5965BK | <input type="checkbox"/> AH5969BK | | • |
| | | | Quick grip straight body | 0.22-0.66" (5.6-16.7mm) | Y | <input type="checkbox"/> AH5965Y | <input type="checkbox"/> AH5969Y | | • |
| | | | Auto grip straight body | 0.33-0.66" (8.3-16.7mm) | BK & W | <input type="checkbox"/> 5266N | <input type="checkbox"/> 5269N | • | • |

Industrial grade flanged inlets & outlets



| Rating A | V/AC | NEMA | Description | Color | Inlet catalog no. | Outlet catalog no. | |
|-------------|------|------|-------------------------------|--------|---|-----------------------------------|---|
| 15 | 125 | 5-15 | Nylon construction, back wire | BK & W | <input type="checkbox"/> AH5278C [†] | <input type="checkbox"/> AH5279C* | • |
| | | | Metal shell, back wire | Steel | <input type="checkbox"/> AH5278 [‡] | <input type="checkbox"/> AH5246 | • |

* UL and CSA Listed, [†] Fed Spec certified, [‡]Only NOM spec

Industrial grade dimensional information: B-16, B-17

Specification information:

Safety grip industrial plugs & connectors: B-24
Quick grip plugs & connectors: B-24
Auto grip industrial plugs & connectors: B-24
Industrial flanged inlets & Flanged outlets: B-25

Color information:

BK (Black), W (White), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32