

Features

- Time-delay
- Current-limiting
- AC & DC rated
- Optional solid state SmartSpot blown fuse indicator
- Time-delay for motor start-ups and transformer inrush currents without nuisance opening
- Current-limiting for low peak let-thru current
- Rejection-style design prevents replacement errors (when used with recommended fuse blocks)
- Easy-to-read label for quick brand recognition and replacement
- Metal-embossed date and catalog number for traceability and lasting identification
- Fiberglass body provides dimensional stability in harsh industrial settings
- High-grade silica filler ensures fast arc quenching and high current limitation

Applications

- Motor circuits
- Mains
- Feeders
- Branch circuits
- Transformers
- Service entrance equipment
- General-purpose equipment

Approvals & Standards

- UL listed to standard 248-12 File E2137
- CSA certified to standard C22.2 no. 248.12
- DC listed to UL standard 248 TRS only

Specifications

- Rated voltage AC UL: 250 V
- Rated voltage DC UL: 160 V
- Frequency: 50/60 Hz
- Ampere Rating: 30 A
- ROHS Compliant: Yes
- Fuse Class: Class RK5
- Speed/Characteristic: Time Delay
- Mounting: Clip
- AC Max I.R./Breaking Capacity: I1: 200 kA
- Connection/Terminal Material: Copper
- Connection/Terminal Type: Ferrule
- Body/Insulating Material: PolyTube

Product Dimensions

- Product Weight: 0.05 lb
- Product Diameter: 0.56 in
- Product Length: 2 in

Packaging Dimensions

- Sell Pack Quantity: 10 Each
- Sell Pack Weight: 0.53 lb
- Sell Pack Width: 2.06 in
- Sell Pack Length: 3 in
- Sell Pack Height: 1.19 in