

# Submersible Pump Cable

## Submersible Pump Cable

600 Volt  
75°C  
3 Conductor w/ Ground



\*Product images are for illustrative purposes only and may differ from the actual product.

### Construction:

- Flat panel

### Category Insulation Description:

- Polyvinyl Chloride (PVC)

### Standards:

- UL Listed per UL83 Type THW construction as deep well submersible pump cable

### Category Conductor Description:

- Annealed bare solid or stranded copper conductors

### Applications:

- For use within well casing supplying power to the submersible pump
- Maximum conductor operating temperatures of -40°C to 75°C in circuits not exceeding 600 volts

Color Code Chart	
# of Conductors	Color
1	Yellow/Black Stripe
2	Yellow/Red Stripe
3	Yellow
4	Yellow/Green Stripe

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Ground Gauge</b>	<b>Insulation Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
P31403	14	3	14	0.045	.1660 x .7690	111
P31203	12	3	12	0.045	.1900 x .8150	160
P31003	10	3	10	0.045	.2100 x .9100	225
P30803	8	3	10	0.06	.2730 x 1.2250	299
P30603	6	3	8	0.06	.3200 x 1.3570	453
P30403	4	3	6	0.06	.3700 x 1.5500	637

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**