

184-15401



Article Number: 184-15401

High Density Slotted Wall Wiring Duct, 1.5" X 4", Non-Adhesive, PVC, Gray, 120ft/Carton

RoHS

Download drawing

Download spec sheet

Base Data

Local Order Number	184-15401
Type	SLHD1.5X4
Color	Gray (GY)
Features and Benefits	<ul style="list-style-type: none">• Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.• Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.• Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.
Product Description	Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
Short Description	High Density Slotted Wall Wiring Duct, 1.5" X 4", Non-Adhesive, PVC, Gray, 120ft/Carton

Product Dimensions

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	1.5 "
Width W (Metric)	38.1 mm
Width W2 (Imperial)	1.5 "
Width W2 (Metric)	38.1 mm
Width W3 (Imperial)	0.16 "
Width W3 (Metric)	4.1 mm
Width W4 (imperial)	0.4 "
Width W4 (metric)	10.2 mm
Width W5 (imperial)	3.6 "
Width W5 (metric)	91.4 mm
Height H (Imperial)	4.07 "
Height H (Metric)	103.4 mm
Mounting Hole Centers (Imperial)	2.0 "

Logistics and Packaging

Quantity Per	carton
Package Quantity	120.0 ft
Package Quantity (Metric)	36.6 m
Carton Quantity	120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes