



UPC Code : 078477728536

Country Of Origin : China

DD00R-DLZ

Decora Smart Dimmer Switch Companion for Multi-Location Dimming with Locator LED, 120/277VAC, 60Hz

The Decora Dimmer Companion is designed for use in a multi-location application only and must be used with a Leviton Decora Smart or Decora Digital dimmer or fan speed control allowing the lighting or fan to be controlled from more than one location. It works using digital circuitry that provides soft fade on/fade off, intuitive operation and a stylish form factor that is compatible with Leviton's Decora wallplates (sold separately). Change the color of at any time by ordering a new face plate color change kit (DDKIT). Face plate colors include white, ivory, light almond, gray, black and brown.

ROHS Compliant : Yes

- PRACTICAL – Turn lights or fan on/off and control brightness or fan level (Must be used with a Decora Smart or Decora Digital dimmer or fan speed control)
- VERSATILE – Can use in 3-way or up to 4 additional locations
- STYLISH – Matches look of main dimmer for seamless appearance
- ROBUST – Dual voltage 120/277VAC, neutral wire required for installation

Have Questions? Search the knowledge base.

Technical Information

Product Features

Action : Rocker Switch for ON /OFF, slide bar for lighting level control

Available Colors : White-W, Ivory-I, Light Almond-T, Gray-G, Black-E, Brown-B

Color : White, Ivory, Light Almond

Color Change Kit : DDKIT

LED Color : Green

Light : LED Locator and Brightness Display

Ordering Notes : Included White, Ivory and Light Almond Color Kit

Preset : Slide bar preserves desired lighting level

Standards and Certifications : CSA, NOM, FCC

Style Name : Decora

Switch Type : 3-Way or Up to
4 Location Applications

Torque Range : 14 – 18 in.-lbs

Type : Companion Device

Voltage : 120/277 VAC

Wallplate : Order Separately

Warranty : 5-Year Limited

Wiring Notes : Neutral required

Features and Benefits

- Decora Dimmer Companion must be used with a Decora Smart or Decora Digital dimmer or fan speed control
- Dual voltage for 120VAC and 277VAC applications
- For use in 3-way or up to 4 additional locations
- LED Locator and Brightness Display tracks main dimmer
- Digital circuitry provides soft fade on/fade off
- Neutral wire required for installation
- White face assembled on device, Ivory and Light Almond faces included

Patents *

US9767973

US7683755

US9329607

US8944859

US10062528

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 • FAX: +1-800-832-9538 • Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 • Telephone: +1-800-469-7890 •
FAX: +1-800-824-3005 • www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 • Tel.: (+52)55-5082-1040 • FAX: (+52)
5386- 1797 • www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.