

Toggle Switches



Versatile toggle switch family with multiple position configurations.

- Available in single or double pole.
- Perfect for industrial equipment or emergency lighting.
- 1/2" mounting hole required.
- **Specifications:** 10 A, 277 V AC / 20 A, 125 V AC

tip: All switches must be installed with a hex nut (provided) behind panel to prevent damage during installation.

Part Number	GSW-10	GSW-11*	GSW-110	GSW-121
Poles	SPST			
Pkg Qty	1/card	1/card	1/card	1/card
Toggle Position	ON-OFF	ON-OFF	ON-OFF	ON-OFF
Terminal Type	Screw	Screw	"O" Ring & Screw	Spade
Rating	1½ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC

*GSW-11 has an ON-OFF faceplate.

Part Number	GSW-12	GSW-13	GSW-120	GSW-117
Poles	SPDT			
Pkg Qty	1/card	1/card	1/card	1/card
Toggle Position	ON-ON	ON-OFF-ON	ON-OFF-ON	(ON)-OFF-(ON)
Terminal Type	Screw	Screw	Spade	Screw
Rating	¾ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC

() Indicates momentary action

Part Number	GSW-14	GSW-15	GSW-16	GSW-123
Poles	DPST		DPDT	
Pkg Qty	1/card	1/card	1/card	1/card
Toggle Position	ON-OFF	ON-ON	ON-OFF-ON	(ON)-OFF-(ON)
Terminal Type	Screw	Screw	Screw	Screw
Rating	1½ HP 125-250 V AC	1½ HP 125-250 V AC	1½ HP 125-250 V AC	1½ HP 125-250 V AC

() Indicates momentary action

Part Number	GSW-17*	GSW-18*	GSW-124	GSW-125	GSW-125BP
Poles	SPST				
Pkg Qty	1/card	1/card	1/card	1/card	10/box
Toggle Position	ON-OFF	ON-OFF	ON-OFF	ON-OFF	ON-OFF
Terminal Type	Screw	6" wire leads	screw	6" wire leads	6" wire leads
Actuator	bat lever	bat lever	short ball	short ball	short ball
Rating	3 A/240 V AC, 6 A/120 V AC	8 A/125 V, 4 A/250 V, 1/3 HP/125 V AC, 10 A/125 V AC	3 A/240 V AC, 6 A/120 V AC	3 A/250 V, 6 A/125 V	3 A/250 V, 6 A/125 V

() Indicates momentary action *GSW-17 & 18 have an ON-OFF faceplate.