



PRODUCT-DETAILS

DP50C3P-F

DP50C3P-F Contactor



General Information	
Extended Product Type	DP50C3P-F
Product ID	1SBX105300R1100
EAN	0804325552356
Catalog Description	DP50C3P-F Contactor
Long Description	DP50C3P-F DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions	
Product Net Depth / Length	83.7 mm

Technical	
Number of Main Contacts NO	3
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Product Name	Definite Purpose Contactors

Technical UL/CSA	
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 3 Hp (208 V AC) Three Phase 15 Hp (220 ... 240 V AC) Single Phase 7.5 Hp (220 ... 240 V AC) Three Phase 15 Hp (440 ... 480 V AC) Three Phase 25 Hp (550 ... 600 V AC) Three Phase 25 Hp
Full Load Amps Motor Use	50 A
Full Load Amps AC Resistance (Heating)	(600 V AC) 65 A

Certificates and Declarations	
cUL Certificate	cUL_E224401
Declaration of Conformity - CE	EN60947-4-1:2001

Container Information	
Package Level 1 Units	1 piece

External Classifications and Standards	
Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
IDEA Granular Category Code (IGCC)	4757 >> Definite Purpose Contactors

Categories	
------------	--

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

